

11 – AUTOMOTIVE LINE

CEMENT LORRY DETERGENT C.L.D. 4021/2

CHARACTERISTICS : this product has been conceived specifically for cleaning inside cement container of cement lorries. Very high penetrating power.

DILUTION : prepare solutions with 5% to 20% (0,5 l - 2 l product in 10 l water) product according to the thickness of the deposits to remove.

USE :

- 1) Wet the surface to clean by using a brush or a low pressure machine;
- 2) Let the product work few minutes, for almost 30 minutes or, anyway, till the moment the product stops to react;
- 3) keep the pH between 1.5 and 2, adding C.L.D.4021/2 IF NEEDED;
- 4) if the pH value remains around 2 without further additions, it means that decrusting is over.
- 5) After treatment, rinse with water abundantly.
- 6) **Avoid the contact of painted surfaces.**

Labelling according to Regulation (EC) No 1272/2008:

Hazard statement Code(s):



Causes severe skin burns and eye damage.
May cause respiratory irritation.

Supplemental Hazard statement Code(s):

not applicable

Precautionary statements:

Avoid breathing vapours.
Wear protective gloves/protective clothing/eye protection/face protection.
IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER/doctor.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Contains:

chloridric acid

Contains (Reg.EC 648/2004):

< 5% non-ionic surfactants

PROFESSIONAL USE ONLY