

04- ECO TECHNICAL LINE

ECO SBLOC

Lubricating unblock grease

- CHARACTERISTICS :**
- suited to unblock any kind of gears, cables, chains, engines, etc.;
 - it prevents problems of filling of metallic material during working time without using a freezing liquid;
 - it contains a very efficient mixture of lubricants, solvents, penetrating agents, corrosion inhibitors and protective agents;
 - it contains anti-oxidising agents to protect metals for long time;
 - long-term protection against corrosive attacks;
 - it does not attack paints, synthetic rubber and plastic materials;
 - its high penetration grants to oil inside pieces, difficult to reach;
 - it works in a short time;
 - perfect lubrication under 0°C temperature too.

DILUTION : **READY FOR USE. SHAKE THE CYLINDER BEFORE USING.**

USE : spray the product directly and uniformly on the surface to oil; let the product work then start to unblock the piece.

Labelling according to Regulation (EC) No 1272/2008:

Hazard statement **Danger** Extremely flammable aerosol.
Code(s): Pressurised container: May burst if heated.



Precautionary statements: Keep out of reach of children.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Contains: Content of VOC ready to use condition: 100,00 %

PROFESSIONAL USE ONLY

DO NOT GET RID OF THE CONTAINER IN THE ENVIRONMENT AFTER USE.

Rel. 1.0 on 03/25/2015

CODES : SPSBLOCM4003471

IT CONTAINS NEW GENERATION PRESSURING AGENTS NOT POLLUTION MAKERS FOR THE OZONE OF THE STRATOSPHERE; THAT'S WAY IT IS CONSIDERED AN ECOLOGICAL PRODUCT.

DO NOT GET RID OF THE CONTAINER IN THE ENVIRONMENT AFTER USE.